



S31B-LE

LoRaWAN Temperature & Humidity Sensor

Overview

The Dragino S31B-LE is a Temperature and Humidity Sensor designed for Internet of Things (IoT) applications. It accurately measures ambient temperature and relative humidity, and transmits the data to an IoT server via LoRaWAN Network.

The sensing element used in the S31B-LE is a fully calibrated, digital temperature and humidity sensor from Sensirion, providing excellent reliability and long-term stability.

S31B-LE has a 2.7" E-Ink display which can provide the reading for the environment status.

S31B-LE supports configurable temperature and humidity alarms, allowing users to receive instant notifications when readings exceed predefined thresholds.

With built-in BLE configuration and wireless OTA firmware updates, the S31B-LE is simple to set up and maintain.


S31B-LE has built-in 8000mAh high-capacity battery which can support for up to 5 years battery life. (depend on uplink interval)



Features

- LoRaWAN v1.0.3
- Configurable uplink interval
- 2.7" E-Ink Display
- Temperature Sensor Range: 0 - 50°C
- Temperature Sensor Accuracy: +0.2 @ 0-80 °C
- Humidity Sensor Range: 0 ~99.9% RH
- Humidity Sensor Accuracy: < 4% RH (between 20% ~ 95%)
- Temperature & Humidity alarm
- Optional Unique Factory Calibrate service
- 8000mAh Li-SOCI2 none-chargeable battery

How does this product work?



Dragino Technology Co., Limited

Room 202, Block B, BCT Incubation Bases (BaoChengTai), No.8 CaiYunRoad
LongCheng Street, LongGang District; Shenzhen 518116, China
Direct: +86 755 86610829 | Fax: +86 755 86647123

WWW.DRAGINO.COM
sales@dragino.com